

Technical Data Sheet

Carbonight® Plus | 62"

A medium-weight, 16oz. Polyester Velvet with a soft hand and matte finish. Ideal for creating theatrical and event drapery, pillows, specialty signage, dressing room curtains, and backdrops.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Raw Material			100% Polyester
Coating			None
Weight		286g./sq.m.	8.4oz./sq.yd.
Construction			Knit
Stretch			N/A
Roll Size		Approx. 60 m	Approx. 65 yds.
Fire Spec	IFR		
Fire Classification	NFPA701Sm		
	CA1237Sm		
	CAN/ULC S109-03		
Suggested Temp Speed			375° - 410° 1-2 Min

Applications

Ceilings	Theatrical	Banners Indoors	Drapery	Decor	Light Boxes	Flags	Trade Show	Signage
	Х	Х	X	Х			X	Х

Ink Printability

Solvent	Eco Solvent	UV	Latex	Dye-Sub Transfer	Dye-Sub Direct
				Х	DG

Available Sizes

Metric (m)	English (inches)
1.6 m	62"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

California 10671 Lorne St. Sun Valley, CA 91352 818-287-3800 **Florida** 7100 TPC Drive. Suite 650 Orlando, FL 32822 407-367-7616 New Jersey 89 Leuning St. Unit D2 South Hackensack, NJ 07606 201-549-1000